


## AC CABLE

It is a universal 3-core power cable designed for electronic and electrical equipment used indoors, manufactured with Class I protection. The product complies with industry standards and European directive requirements. It features high-quality craftsmanship, durability, flexibility, and the ability to operate within a wide temperature range. Available in multiple versions, allowing for an optimal solution in any situation.



## TECHNICAL CHARACTERISTICS

Group	Parameter	Value
Purpose and functionality	Type	Power cable for electrical and electronic devices
	Model	BDKB - SW - P3 - xxM
	Shape	Round
	Safety	Class I insulation (with grounding)
	Color	Black
	Length	1.2 m   1.5 m   1.8 m   3 m   5 m
	Mounting	Potting assembly
Design	Number of wires	3
	Wire colors	Brown, blue, yellow-green
	Conductor cross-section	0.75 mm <sup>2</sup>
	Conductor construction	0.75 mm <sup>2</sup> = 24×0.2 mm
	Wire material	Class 5 copper
	Resistance	26 Ω/km
	Insulation thickness (inner/outer)	0.6/0.8 mm
	Outer diameter of the cable	6.5 mm
	Wire insulation material	PVC (polyvinyl chloride)
	Cable insulation material	PVC (polyvinyl chloride)
	Type	H05VV-F
Load capacity	Cable voltage withstand (Uo/U)	300 / 500V
	Rated voltage	250 VAC / 50 Hz
	Rated current	10 A
	Insulation test voltage	2000 VAC
Input connection	Temperature range	-25 to +70°C
	Power plug type	Straight
	Mains plug	SEV 1011 D13
	Standard	CHE
Output connection	Plug contacts	Nickel-plated
	Plug color	Black
	Device plug	Straight
	Type	C13
Certification	Plug color	Black
	Compliance with standards	IEC60227 Cable Mains plug IEC60884-1 Device plug IEC60320-7
Features	Approval marks	CE, RoHS, REACH
	Warranty	5 years
	Packing	50 items

### MAINS PLUG

**1.** The (SW) SEV 1011 D13 mains plug is a grounded connection used in Switzerland, compliant with the SEV 1011 D13 standard. It is compatible with type J sockets, which fit a plug with three round pins. It has three pins: two round for the phase and neutral wires and one grounding. It is intended for devices requiring grounding and meeting protection class I. The rated load capacity of the plug is 10 A at a voltage of 250 VAC. The plug pins are nickel-plated, which ensures reliable electrical contact and protection against corrosion. The wire is secured using the hot plastic casting method, which guarantees mechanical and environmental durability.

### CABLE


**2.** A 3-wire cable with flexible insulation made of polyvinyl chloride (PVC) ensures safety and ease of use. Each conductor within the cable is additionally insulated, and the cores are made of multi-stranded copper wire, providing high flexibility. The cable meets the requirements of the IEC60227 standard and is manufactured in black. The outer insulation sheath is resistant to mechanical impact and multiple bending cycles. Detailed technical data, conductor diameters, insulation thicknesses, and copper core parameters are provided in the table.

### DEVICE PLUG





**3.** C13 (P3) plug is a standardized IEC connector (IEC 60320 C13) and is widely used in medium and high-power electronic devices. It is used in desktop computers, servers, UPS power supplies, desktop power supplies, printers, monitors and RTV/AGD devices. It provides a 3-wire connection (with power earth), intended for devices in protection class I, i.e. requiring grounding. Its design prevents incorrect insertion into the socket, ensuring safety and protection against incorrect inserting.

MARKING SYSTEM


BDKAB - SW - P3 - 1.2 M




VARIANTS

Mains plug SEV 1011 D13	Length	Conductor cross-section	Device plug C13
		 0.75 mm²	
	1.2 m		
	1.5 m		
	1.8 m		
	3 m		
	5 m		

MECHANICAL SPECIFICATION



TYPES OF ELECTRICAL OUTLETS USED AROUND THE WORLD



Type E plugs are used in Belgium, France, Poland, Slovakia, the Czech Republic, Tunisia, and Morocco. The pins of the Type E plug are 19 mm long and are spaced 19 mm apart.

Type F plugs are used in the Netherlands, Germany, Austria, Sweden, Norway, Finland, Portugal, Spain, Turkey, and Eastern Europe. They are also found in some countries in Africa, Asia, and South America.

The most commonly encountered outlet in Europe is the Type F socket, also known as Schuko (from the German "Schutzkontakt"). This variant is similar to Type C but has two metal contacts on the top and bottom to provide contact with the ground. This is also referred to as protective grounding. This plug is round, with bulges on the left and right sides.

AVAILABLE MODELS

Model	Name	Length [m]	EAN
BDKAB-SW-P3-1.2M	Power cable 1.2m SEV 1011 D13 (SW) [10A] - IEC C13 [10A]; H05VV-F 3×0.75mm <sup>2</sup>	1.2	
BDKAB-SW-P3-1.5M	Power cable 1.5m SEV 1011 D13 (SW) [10A] - IEC C13 [10A]; H05VV-F 3×0.75mm <sup>2</sup>	1.5	
BDKAB-SW-P3-1.8M	Power cable 1.8m SEV 1011 D13 (SW) [10A] - IEC C13 [10A]; H05VV-F 3×0.75mm <sup>2</sup>	1.8	5904139605998
BDKAB-SW-P3-3.0M	Power cable 3.0m SEV 1011 D13 (SW) [10A] - IEC C13 [10A]; H05VV-F 3×0.75mm <sup>2</sup>	3.0	
BDKAB-SW-P3-5.0M	Power cable 5.0m SEV 1011 D13 (SW) [10A] - IEC C13 [10A]; H05VV-F 3×0.75mm <sup>2</sup>	5.0	

