

UT202



[Enlarge](#)



Registered Design No.: 0311320.4

[Download Manual](#)

Digital Clamp Multimeters

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2V/20V/200V/600V	±(0.8%+1)
AC Voltage	2V/20V/200V/600V	±(1.2%+5)
AC Current	2A/20A/200A/400A	±(1.5%+5)
Resistance	200W/2kW/20kW/200kW/2MW/20MW	±(1%+2)
Temperature(°C)	-40°C~1000°C	±(1%+3)
Temperature(°F)	-40°F~1832°F	±(1%+6)
Special Functions		
Auto Ranging	✓	
Diode	✓	
Continuity Buzzer	✓	
Max Hold	✓	
Data Hold	✓	
Full Icon Display	✓	
Sleep Mode	✓	
Low Battery Display	✓	
Input Impedance for DC Voltage Measurement	Around 10MW	
Max Display	1999	

GENERAL CHARACTERISTICS

Power	3V Battery (AAA) x 2
LCD Size	35.6 x 18mm
Product Colour	Red and Grey
Product Net Weight	220g
Product Size	210 x 75.6 x 30mm
Standard Accessories	Test Lead, Batteries, English Manual, Point Contact Temperature Probe, Carrying Bag
Optional Accessories*	Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2)
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	40 pcs
Standard Carton Measurement	485 x 415 x 290 mm (0.058 CBM Per Standard Carton)
Standard Carton Gross Weight	15kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)