



























规格代号	外型	项目	外型尺寸 (mm)	接点形成	吸合安匝 (AT)	释放安匝 (AT)	接触电阻 (mΩ)	绝缘电阻 (MΩ)	介质耐压 (VAC)	触点负荷	触 点				环境温度	电气寿命	结构尺寸
											动作时间 (ms)	回跳时间 (ms)	释放时间 (ms)	最大工作频率			
GAG-2A			Φ20×10	动合	10~35	≥8	≤200	≥100	100	12VDC 0.01A	≤0.8	≤0.3	≤0.15	10	-10℃~+40℃	1×10 <sup>6</sup>	
GAG-2B			Φ20×12	动合	10~35	≥8	≤200	≥100	100	12VDC 0.01A	≤0.8	≤0.3	≤0.2	10	-10℃~+40℃	1×10 <sup>6</sup>	
GAG-2C			Φ20×14	动合	10~40	≥8	≤200	≥100	100	12VDC 0.01A	≤0.8	≤0.4	≤0.2	10	-10℃~+40℃	1×10 <sup>6</sup>	
GAG-2			Φ25×16	动合	15~35	≥10	≤200	≥100	100	12VDC 0.01A	≤0.8	≤0.4	≥0.2	10	-10℃~+40℃	1×10 <sup>6</sup>	
		转换		40~55	10~2 5	≤500											
GAG-3			Φ3×20	动合	25~50	返回系数 ±30%	≤200	≥100	150	12VDC 0.05A 0.03A	≤0.8	≤0.4	≤0.2	10	-10℃~+40℃	1×10 <sup>6</sup>	
		转换		35~55	返回系数 ±30%	≤400											
				Φ3×28	动合	20~70	15~45	≤200	≥100	250	24VDC 0.1A	≤5	≤2	≤1	10	-10℃~+40℃	1×10 <sup>6</sup>
GAG-4A			Φ4×28	动合	35~70	≥25	≤300	≥100	300	24VDC 0.1A	≤5	≤2	≤1	10	-10℃~+40℃	1×10 <sup>6</sup>	
GAG-4			Φ4×38	动合	50~80	≥25	≤200	≥100	300	24VDC 0.2A	≤1.5	≤0.7	≤0.3	50	-10℃~+40℃	1×10 <sup>6</sup>	
			Φ4×36	转换	45~65	≥20	≤200	≥100	300	24VDC 0.1A	≤1.7 ≤2.5	≤1.0	≤0.5 ≤0.6	50		1×10 <sup>6</sup>	
GAG-5			Φ5×50	转换 动合	80~120	≥30	≤200	≥300	300	24VDC 0.5A	≤12	≤1	≤0.5	100	-10℃~+40℃	1×10 <sup>6</sup>	
GAG-6			Φ8×40	动合	100~300	≥35	≤200	≥300	2000	220VAC 0.5A	≤1	≤0.8	≤0.3	50	-10℃~+40℃	1×10 <sup>6</sup>	
GAG-8			Φ8×50	转换	120~330	≥60	≤200	≥100	1000	220VAC 1A	≤1 ≤12	≤0.8 ≤1	≤0.3 ≤0.4	100	-10℃~+40℃	1×10 <sup>6</sup>	
		动合															
GAG-7			Φ7.5×50	转换	200~470	≥135	≤100	≥300	500	220VAC 1A	≤1	≤0.5	≤0.3	50	-10℃~+40℃	1×10 <sup>6</sup>	